



High-Current, Buried-Arc Transfer Welding

D-Arc





DAIHEN Corporation

High-Current, Buried-Arc Transfer Welding

Revolutionary Arc Control Delivers High-Performance, Thick Plate Welding

DAIHEN's D-Arc is the world's first welding solution delivering stable, high-current control required for buried-arc transfer. Our exclusive technology enables high-efficiency, thick-plate welding with the high-quality required in large structures such as buildings, bridges, marine vessels and construction equipment. An innovative alternative to conventional, multi-layer welding.

D-Arc




D-Arc, Daihen-Exclusive Technology Delivers Thick-Plate Welding with Unmatched Quality & Efficiency

High-Current, Buried-Arc Transfer Welding with Current Control provided by Welbee: Welding's Best Electronic Engine






Buried-Arc Welding



In buried-arc welding, the heat of the electrical arc serves to locally melt the base metal as well as melt the wire filler metal that is being buried into the weld. The heat reaches well inside the substrate to achieve deep penetration.












Faster welding speed reduces production cost

Comparison	Conventional Multi-Layer Welding	D-Arc Welding	Comparative Bar Graph
Welding Method	6 passes 	1 pass 	<div>Welding Cost per 1 m</div> 

Enhanced arc-control ensures high-quality welds


Comparison	Conventional Multi-Layer Welding	D-Arc Welding
Weld Quality	<div>Weld Bead Appearance</div>  <div>Ununiform bead distribution, large spatter pattern</div>	<div>Weld Bead Appearance</div>  <div>Uniform bead distribution, no spatter mark</div>

D-Arc answers the challenges of thick-plate welding

Comparison	Conventional Multi-Layer Welding	D-Arc Welding	Comparative Bar Graph
Simplifies edge preparation	Requires large grooving 	Requires no large grooving 	<div>Grooving Area Needed in Preparation</div> 
Welds thick plate in one pass	Requires multiple passes 	Requires reduced passes 	<div>1 m Weld Time</div> 
Reduces weld distortion	Much weld distortion 	Reduced weld distortion 	<div>Welding Distortion, Angular</div> 

D-Arc is the marriage of a high-output welding system with the stable current control of our exclusive Welbee technology

D-Arc combines the precise control of Welding's Best Electronic Engine (Welbee) with our high-output welding system. Purpose-built for high-current and high-speed, D-Arc delivers the world's first high-current, buried-arc welding with stable, high-quality results.





Welbee, the precision waveform control achieved successful stabilization of high current buried-arc


Daihen's exclusive Welbee technology provides the precise welding current waveform control necessary for stable, high-current, buried-arc transfer welding

Voltage Amplitude Control

Alternating between low and high voltage delivers two (2) transfer modes, resulting in the deep penetration and stable weld pool required.



Application examples





Parameter	Specification	Welding Joint	Cross-Section Metallography
Plate thickness	9mm		
Weld edge geometry	I groove		
Gap	4mm		
Backing	Ceramic		
Welding current	430A		
Welding voltage	40V		
Welding Speed	30cm/min		

Parameter	Specification	Welding Joint	Cross-Section Metallography
Plate thickness	19mm		
Weld edge geometry	Bevel groove		
Gap	0mm		
Backing	Ceramic		
Welding current	580A		
Welding voltage	48V		
Welding Speed	24cm/min		

Parameter	Specification	Welding Joint	Cross-Section Metallography
Plate thickness	35mm		
Weld edge geometry	Double V groove		
Gap	0mm		
Backing	None		
Welding current	620A		
Welding voltage	47V		
Welding Speed	30cm/min		

Parameter	Specification	Welding Joint	Work Posture	Cross-Section Metallography
Plate thickness	16mm			
Weld edge geometry	I groove			
Gap	0mm			
Backing	None			
Welding current	605A			
Welding voltage	44V			
Welding Speed	30cm/min			

Specification



D-Arc Welding		
Parameter	Specification	Remarks
Shield gas	CO ₂ 100%	Reference flow rate: 30 L/min
Wire	YGW11,18	
Wire diameter	(1.2), 1.4, (1.6)mm	Packed wire only
Base material	Steel, 400 MPa yield strength Steel, 490 MPa yield strength	Stainless steel, excluding high alloy and special steels
Joint type	Square, fillet	
Work Posture	Downward	
Edge type	I, V, Y, bevel, double V, etc.	
Backing	Steel, copper, ceramic	
Plate thickness	6~35mm	19 mmt max: single-layer, thorough 19-35 mmt: front-back, double-layer
Reference welding rate	30±10cm/min	

Welding Power Supply	
Parameter	Specification
Model	WB-DPS
Running method	Dual parallel
Welding mode	D-Arc, DC CO ₂
Rated input voltage	200V/220V (common for 50/60 Hz)
Number of phase	3-phase
Rated input power	Per power supply unit: 27.4 kVA (25.7 kW); Parallel run: 50.3 kVA (45.4 kW)
Rated duty cycle	100%
Rated output current range(parallel run)	650A
Rated output Voltage range(parallel run)	55V
Rated output current (parallel run)	40~650A
Output current range (parallel run)	12~60V
Maximum No-load voltage	111V / 123V
External dimensions	W395×D710×H810mm, excluding eye bolts
Weight (per unit)	72kg

Wire Feeder		
Parameter	Specification	
Model	Pull feeder: DF-PL	Push feeder: DF-PS
Wire diameter	(1.2), 1.4, (1.6)mm	
Wire	Solid wire	
Wire feeding rate	70 m/min max	
External dimensions	W328×D297×H266mm	W268×D646×H322mm
Weight	9kg	19kg

Welding Torch	
Parameter	Specification
Model	DTWH6500S
Wire diameter	(1.2), 1.4, (1.6)mm
Rated current	650A
Duty cycle	100%
Type of cooling	Liquid cooled
Weight	1kg